

Nirantar UPS-621V



Electrifying recharge speed. Only UPS with 33% faster recharging. Superior reliability , coupled with advanced backup facility.

MRP Rs. : 2,295.00

Features / Specifications

Features :	33% Faster recharging Protects you from data loss Wide input voltage range Generator compatible Automatic voltage regulator for Boost & Buck Auto restart while AC recovery
Capacity :	600VA/360W
Microprocessor Controlled :	Microprocessor controlled to guarantee high reliability
Input Voltage :	230VAC
Input Voltage Range :	140-300VAC
Input Frequency :	45-65 Hz (Auto Sensing)
Output Voltage :	230VAC
Output Voltage Regulation (Batt.) :	195-253V
Output Frequency :	50Hz or 60Hz
Output Frequency Regulation (Batt.) :	+/- 1Hz
Output Waveform :	Modified Sine-wave
Battery Type :	12V7AH x 1
Recharge Time :	6 hours to 90% at normal mode
Transfer Time :	4-8ms
LED Indicator :	Green LED for various indication modes
Audible Alarm :	Beeper with various beeper modes
Full Protection :	Discharge, overcharge, and overload protection
Power Outlets :	3-Pin x 3
Dimension (D x W x H) :	287 x 100 x 142 mm
Net Weight :	4.25 Kg.
Operating Environment :	0°C - 40°C
Noise Level :	Less than 40dB
Warranty :	2 Years (1 Year for battery)